

# TwistPort™ Adaptor

## for UBNT Rocket® Prism 5AC and airFiber® 5X

TPA-PAF makes Rocket® Prism 5AC, Rocket® Prism 5AC Gen2, airFiber® 5X and airFiber® 5XHD compatible with any TwistPort™ antenna. TPA-PAF contains well protected space for GPS antenna that comes with UBNT® Radios.

Connecting and disconnecting the radio from the TwistPort™ Adaptor is very simple and requires no tools.



### TECHNICAL DATA

Antenna Connection	TwistPort - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA and 1x SMA for GPS
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.34 Kg / 0.75 lbs – single unit 0.52 Kg / 1.14 lbs – single unit incl. package 11.2 Kg / 24.7 lbs – carton (20 units)
Single Unit	Retail Box: 20.4 × 13.7 × 10.2 cm
20 Units	Carton Box: 105.0 × 29.0 × 23.0 cm

### PERFORMANCE

Frequency Range	5180 - 6400 MHz
Polarization	Dual Linear H + V
VSWR Max	1.8
Impedance	50 Ohm

### COMPATIBLE WIRELESS PLATFORMS

RF elements®	any TwistPort™ Antenna
Ubiquiti Networks®	Rocket® Prism 5AC, Rocket® Prism 5AC Gen2 airFiber® 5X, airFiber® 5X-HD

### PACKAGE CONTENTS

- TwistPort™ Adaptor
- AF5X Mount Adaptor

### PRODUCT DIMENSIONS

